


平鋼 最小曲げ半径



(フランジ曲げ)

t \ W	38	44	50	65	75	90	100	125	150	180	200	250	300
3	200	300	400										
4.5	170	170	200	450									
6	170	170	170	350	450	500	500	800	1000				
8	170	170	170	350	450	500	500	800	1000				
9	170	170	170	350	450	500	500	800	1000				
12	170	170	170	350	450	500	500	1000	1200	2000	2500		
16	170	170	250	400	450	500	600	1100	1200	2000	2500	2500	2500
19	170	170	250	500	500	500	600	1100	1200	2000	2500	2500	2500
22	200	200	300	500	500	500	700	1000	1500	2000	2500	2500	2500
25	200	200	300	500	500	500	700	1300	1500	2000	2500	2500	2500
28	200	200	300	500	500	500	700	2000	2000	2500	3000	3500	3500
32	250	250	300	500	500	500	700	2000	2000	2500	3000	3500	3500
36	300	300	400	500	500	500	700	2000	2000	3000	3000	3500	3500
44	400	400	500	500	500	500	700	2000	2000	3000	3000	3500	4000
50	400	400	500	500	500	500	1000	2000	2000	3000	3000	4000	4000

備考

- つかみ代 小型機 400mm (200mm x 2)
- 中型機 600mm (300mm x 2)
- 大型機 (A) 1000mm (500mm x 2)
- 大型機 (L) 1600mm (800mm x 2)
- 大型機 (LL) 1600mm (800mm x 2)

※ つかみ代についてはお問い合わせ下さい

※ 変形形状は別紙「変形および検査方法」をご覧ください。