





C T形鋼 最小曲げ半径

			
H x B x t1 x t2	フランジ曲	外 曲	内 曲
50 x 50 x 5.0 x 7.0	300	300	350
50 x 100 x 6.0 x 8.0	500	500	550
62.5 x 60 x 6.0 x 8.0	300	300	400
62.5 x 125 x 6.5 x 9.0	500	500	600
75 x 75 x 5.0 x 7.0	400	400	500
74 x 100 x 6.0 x 9.0	500	500	600
75 x 150 x 7.0 x 10.0	1500	500	600
87.5 x 90 x 5.0 x 8.0	500	500	600
87.5 x 175 x 7.5 x 11.0	1500	500	600
100 x 100 x 5.5 x 8.0	500	500	600
97 x 150 x 6.0 x 9.0	1500	500	600
100 x 200 x 8.0 x 12.0	2000	1000	1200
125 x 125 x 6.0 x 9.0	1500	1000	1200
122 x 175 x 7.0 x 11.0	1500	1000	1700
125 x 250 x 9.0 x 14.0	2500	1000	1700
150 x 150 x 6.5~9.0	1500	1200	1700
147 x 200 x 8.0 x 12.0	2500	1500	1700
150 x 150 x 10.0 x 15.0	1500	1200	1700
175 x 175 x 7.0 x 11.0	1500	1500	2000
170 x 250 x 9.0 x 14.0	3000	1500	2000
175 x 350 x 12.0 x 19.0		2000	2000

備 考

※ つかみ代についてはお問い合わせ下さい

※ 変形形状は別紙「変形および検査方法」をご覧ください。